

Technologia dla wygody

COMFORT-ORIENTED TECHNOLOGY
New products 2014 / Motors and control systems

Flush-mounted switches

667102 Switch - flush-mounted / WHITE / 1Sf
Type: with output latching

667103 Switch - flush-mounted / WHITE / 1Sf
Type: without output latching

**1Sf**

/ flush-mounted
/ mechanic lock
/ contraction capability: 10A/250V
/ screw clamps
/ color: white
/ dimensions: 82x82x30 [mm]

MAGNETIC Deluxe series

1711701 Single-channel wall transmitter / WHITE / 1Rw

**1Rw**

/ set contains magnetic wall holder
/ wireless transmitter
/ wall-mounted
/ power supply: 3V, three battery units CR2430
/ can control single motor, or a group of up to 20 motors
/ signal: 10mW
/ working distance: up to 200m (218yd) outdoors
and 35m (38yd) indoors
/ operating temperature: 0°C/50°C (273°F/323°F)
/ dimensions: 85x85x15 [mm]
/ IP 30

MAGNETIC Deluxe series

1711702 2-channel wall transmitter / WHITE / 2Rw

**2Rw**

/ set contains magnetic wall holder
/ wireless transmitter
/ wall-mounted
/ power supply: 3V, three battery units CR2430
/ can control single motor, or a group
of up to 20 motors on each channel
/ signal: 10mW
/ working distance: up to 200m (218yd) outdoors
and 35m (38yd) indoors
/ operating temperature: 0°C/50°C (273°F/323°F)
/ dimensions: 85x85x15 [mm]
/ IP 30

MAGNETIC Deluxe series

1711715 15-channel wall transmitter / WHITE / 15Rw

**15Rw**

/ set contains magnetic wall holder
/ wireless transmitter
/ wall-mounted
/ built-in LCD display
/ power supply: 3V, three battery units CR2430
/ can control single motor, or a group
of up to 20 motors on each channel
/ signal: 10mW
/ working distance: up to 200m (218yd) outdoors
and 35m (38yd) indoors
/ operating temperature: 0°C/50°C (273°F/323°F)
/ dimensions: 85x85x15 [mm]
/ IP 30

**CE RoHS**

All devices operate
on frequency: 433 MHz ± 100kHz

MAGNETIC Deluxe series**1701800** Single-channel remote control / WHITE / 1R**1R**

/ set contains magnetic holder
 / wireless transmitter
 / power supply: 3V, single battery unit CR2450
 / can control single motor, or a group of up to 20 motors
 / signal: 10mW
 / working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
 / operating temperature: 0°C/50°C (273°F/323°F)
 / dimensions: 130x44x10 [mm]
 / IP 30

**MAGNETIC Deluxe series****1701802** 15-channel remote control / WHITE / 15R**15R**

/ set contains magnetic holder
 / wireless transmitter
 / built-in LCD display
 / power supply: 3V, single battery unit CR2450
 / can control single motor, or a group of up to 20 motors on each channel
 / signal: 10mW
 / working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
 / operating temperature: 0°C/50°C (273°F/323°F)
 / dimensions: 130x44x10 [mm]
 / IP 30

**MAGNETIC Classic series****1701603** Single-channel remote control / WHITE / 1RT time programming**1RT**

/ set contains magnetic wall holder
 / wireless transmitter
 / time programming function
 / built-in manual, automatic and random mode
 / built-in LCD display
 / power supply: 3V, single battery unit CR2450
 / can control single motor, or a group of up to 20 motors
 / signal: 10mW
 / working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
 / operating temperature: 0°C/50°C (273°F/323°F)
 / dimensions: 130x44x10 [mm]
 / IP 30

**MAGNETIC Classic series****1711673** 15-channel wall transmitter / WHITE / 15Rw**15Rw**

/ set contains magnetic wall holder
 / wireless transmitter
 / wall-mounted
 / built-in LCD display
 / power supply: 3V, single battery unit CR2430
 / can control single motor, or a group of up to 20 motors
 / signal: 10mW
 / working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
 / operating temperature: 0°C/50°C (273°F/323°F)
 / dimensions: 80x80x11 [mm]
 / IP 30

**CE RoHS**

All devices operate
 on frequency: 433 MHz ± 100kHz



Roller shutters

Built-in obstacle detection sensor in motors from BD series makes roller shutters completely safe – movement will be stopped whenever any obstacle gets in its way.

For narrow roller shutters use our special 45S motor – it's only 33cm long.




Projection screens

Use the best equipment - 25TE series motors (power supply: 110 – 230V) and 25LE series motors (with built-in battery).



Awnings

Automation for wind or sun protection increases the comfort of everyday living. It also protects itself from any damage (vibration sensor protects from strong wind).



House alarm

In case of detection of smoke, gas, movement etc., or in case of any other unwanted condition that is registered, roller shutters will do as programmed (open or close).



Lighting

Lighting can be controlled manually as well as automatically. Yooda system can switch it on or off depending on preprogrammed time.

Power sockets

This solution allows user to control every device operating on electric power: lamps, fans, electric radiators etc.



CE RoHS

All devices operate
on frequency: 433 MHz ± 100kHz

Horizontal blinds

EVY motor series allow user to wirelessly control all kinds of blinds thanks to built-in radio receiver and impulse control mode. They also allow user to set third limit – favorite position.

Roller blinds

16 series motors are equipped in radio receiver, built-in battery (16LE), and also head, that is compatible with many of the most popular cosset systems for roller blinds.



Curtains

Yooda Smart Control is fully compatible with all of the E and LE Cortino motors with radio receiver, what makes it possible to control all automated curtains.



Garage doors

GAMMA X control unit combined with backup power supply assure safety of usage and allow user to open the gate even in situation of power outage.




Swing and sliding gates

Ideal for automation of gates are extension radio modules that allow for the user to use standard control system of YOODA.

Seria **SMART CONTROL****1190150 Intelligent control unit**

- / compatible with all YOODA, Cortino and TenPilot products
- / operated by smartphones or tablets with Android or iOS systems or any personal computer
- / group control function for all connected devices
- / system allows for "scenarios" to be programmed, making specific group of devices to run on specific time of the day – the same way as a "alarm clock" works
- / operates on local Wi-Fi network
- / Control unit is equipped in built-in server
- / code encryption
- / application available in Polish and English language



NUXO Series

1702160 2-channel remote control
WHITE / 1x2R

1702160B 2-channel remote control
BLACK / 1x2R_B

/ Unused channels can be disabled



1x2R

/ set contains magnetic wall holder
/ wireless transmitter
/ built-in antiglare LCD display
/ power supply: 3V, two battery units AAA
/ can control single motor, or a group of up to 20 motors on each channel
/ signal: 10mW
/ working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
/ operating temperature: 0°C/50°C (273°F/323°F)
/ dimensions: 130x44x10 [mm]
/ IP 30

**NUXO Series**

1702162 30-channel remote control
WHITE / 15x2R

1702162B 30-channel remote control
BLACK / 15x2R_B

/ Unused channels can be disabled



15x2R_B

/ set contains magnetic wall holder
/ wireless transmitter
/ built-in antiglare LCD display
/ power supply: 3V, two battery units AAA
/ can control single motor, or a group of up to 20 motors on each channel
/ signal: 10mW
/ working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
/ operating temperature: 0°C/50°C (273°F/323°F)
/ dimensions: 130x44x10 [mm]
/ IP 30

**BRAVA Series**

1711103 Single-channel key-ring remote / 1Rk_Bw (black/white)

1711106 Single-channel key-ring remote / 1Rk_Wb (white/black)

1711108 Single-channel key-ring remote / 1Rk_B (black)

1711107 Single-channel key-ring remote / 1Rk_W (white)



1Rk_W

/ remote in form of a handy key-ring
/ wireless transmitter
/ power supply: 12V, single battery unit 27A
/ can control single motor, or a group of up to 20 motors
/ signal: 10mW
/ working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
/ operating temperature: -20°C/+50°C (-253°F/323°F)
/ dimensions: 63x35x17 [mm]
/ IP 44

**GAMMA X Series**

1610121 single-channel control unit / 1Cw_LPI

1Cw_LPI

/ allows photoelectric cell connection
/ allows different types of connection for photoelectric cells (NO, NC)
/ different scenarios for motor reaction after photoelectric cell signal
/ compatible with wall or key switches
/ lighting connection (up to 250W)
/ single motor connection (up to 500W)



/ different control modes (regular, impulse)
/ automatic gate shutting function with timer
/ memory storage for up to 20 transmitters
/ working distance: up to 200m (218yd) outdoors and 35m (38yd) indoors
/ supply voltage: 230V/50Hz
/ dimensions: 131x80x44 [mm]
/ IP 30




CE RoHS


All devices operate on frequency: 433 MHz ± 100kHz

35 BD Series

35BD series tubular motor
with built-in obstacle detection sensor




BD motors work with
soft roller shutters hangers





Index	Symbol	Torque	RPM	W	A	No. of rotations	Ø	L1 mm	L2 mm	Weight kg
12306BD	35BD 6Nm/28	6 Nm	28	144	0,62	∞	35	577	564	1,43
12310BD	35BD 10Nm/17	10 Nm	17	148	0,65	∞	35	577	564	1,43
12313BD	35BD 13Nm/14	13 Nm	14	121	0,53	∞	35	577	564	1,58

45 BD Series

45BD series tubular motor
with built-in obstacle detection sensor



BD motors work with
soft roller shutters hangers



Index	Symbol	Torque	RPM	W	A	No. of rotations	Ø	L1 mm	L2 mm	Weight kg
12110BD	45BD 10Nm/15	10 Nm	15	113	0,48	∞	45	620	608	1,88
12120BD	45BD 20Nm/15	20 Nm	15	161	0,69	∞	45	620	608	2,07
12130BD	45BD 30Nm/15	30 Nm	15	200	0,87	∞	45	670	658	2,40
12140BD	45BD 40Nm/12	40 Nm	12	218	0,95	∞	45	670	658	2,76

CE RoHS





Sukces
Technology Group

www.sukcesgroup.pl

Sukces Technology Group - Dziemiańczuk sp.j.

Produkcyjna 2, 16-010 Wasilków, PL

T: + 48 85 87 84 700

Distributors address:

