
Control System

DC2900
Emitter Specification

Version NO. : A/00

T Type specification



DC2900
Single - channel emitter

DC2900 Back side


T Technical support

Technical specification	Fucntion instruction
• Input voltage: 3V(CR2450) • Transmitting frequency: 433MHz • Transmitting power: 10 milliwatt • Operating temperature: -10°C—50°C • Transmssion distance: 200 meters open office, 35 meters on two walls	DC2900 is Single channel emitter CAUTION RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS Notice: transmitter do not exposed to moisture and strike, so as not to affect life.When you use transmitter, if found emission distance obviously short or less sensitive, please change another same new battery. Please have batteries for recycling.

A Additional function — Matchable R tubular motor setting up


⚠ Delete all the datas of the motor and the new emitter has been programmed.

During the settings,the time between two operation must be shorter than 4s,otherwise it will quit the setting



A Additional function — Matchable DC1680 setting up

⚠ During the settings,the time between two operation must be shorter than 6s,otherwise it will quit the setting



A Additional function — Matchable DC136 setting up

⚠ During the settings,the time between two operation must be shorter than 10s,otherwise it will quit the setting

